



Blades

KD482/602/722

Ventrac KD **Power Angle Dozer Blades** have working widths of 48, 60, and 72 inches (122, 152, 183 centimeters). All control functions are performed with the S.D.L.A. control for raising and lowering the blade or angling it left or right. Adjustable cast iron skid shoe discs accommodate dozing at selected heights, such as moving snow on gravel driveways.

The blades can be operated in a trip position for plowing or in a locked position for grading or leveling of material. The Ventrac Mount System allows you to connect to the blade quickly and easily, without tools.

Ventrac Power Angle Dozer Blades are versatile, laborsaving attachments designed for any number of jobs. From grading, leveling, and backfilling ground to plowing snow, moving material, or cleaning an area, the Ventrac KD series blades are up to the task.



Adjustable cast iron skid shoe discs



Standard Features:

- Hydraulic angle left or right
- Trip Pin allows locked operation
- Reversible Cutting Edge
- Ventrac Mount System
- Adjustable Cast Iron Skid Shoe Discs
- Greasable center pivot

Optional Accessories:

- Polyurethane Cutting Edge
- Hardened Cutting Edge



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC (836.8722)
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com

Specifications

Blades

KD482/602/722

	KD482	KD602	KD722
Stock Code	39.55251	39.55252	39.55253
Hydraulic Power Angle	Standard	Standard	Standard
Spring Trip	Mechanical On/Off	Mechanical On/Off	Mechanical On/Off
Hydraulic Cylinder Bore and Stroke	2 x 8 inches (5 x 20 cm)	2 x 8 inches (5 x 20 cm)	2 x 8 inches (5 x 20 cm)
Max Angle (Left/Right)	30 Degrees	30 Degrees	30 Degrees
Ground Clearance	13 inches (33 cm) @ 0 deg.	13 inches (33 cm) @ 0 deg.	13 inches (33 cm) @ 0 deg.
Adjustable Skid Shoes	Standard	Standard	Standard

Optional Accessories

Polyurethane Cutting Edge	44.0207	44.0205	44.0206
Hardened Cutting Edge	78.0057	78.0058	78.0059

Dimensions

Length	27 inches (69 cm)	27 inches (69 cm)	27 inches (69 cm)
Width	48 inches (122 cm)	60 inches (152 cm)	72 inches (183 cm)
Height	22 inches (56 cm)	22 inches (56 cm)	22 inches (56 cm)
Working Width - 0 degrees	48 Inches (122 cm)	60 inches (152 cm)	72 inches (183 cm)
Working Width - 30 degrees	42 inches (107 cm)	52 inches (132 cm)	62 inches (158 cm)
Weight	163 lbs (74 kgs)	203 lbs (92 kg)	225 lbs (102 kg)
Shipping Weight	207 lbs (94 kgs)	272 lbs (123 kgs)	282 lbs (128 kgs)
Shipping Dimensions (LWH)	64x24.5x15.6 inches (163x62x40 cm)	76x24.5x15.6 inches (193x62x40 cm)	88x24.5x15.6 inches (224x62x40 cm)

All specifications subject to change without notice or obligation



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com